

GSR's PROCAT-Project: Technical de-risking of deep sea mining equipment

Global Sea Mineral Resources

BGR, Hannover | 29.10.2018

Kris De Bruyne



DEME

Dredging, Environmental
& Marine Engineering

A step-by-step approach towards
a prototype mining vehicle



GSR

This presentation contains proprietary and/or confidential information.
Any disclosure, copying, distribution or use of this information/the ideas incorporated is strictly prohibited. This information is not to be considered as a representation of any kind.
Any intellectual and industrial property rights and any copyrights with regard to this presentation, and the information therein, shall remain the sole property of DEME.



CONTENT OF THE PRESENTATION



CONOPS

**CONCEPT
DESIGN
CHOICE**


PROCAT#1

PROCAT#2

COMPASS




CONOPS | FATAL FLAW- & 'INFORMATION' GAP ANALYSIS




DEME | OCEANWISLAND FOR THE FUTURE



CONCEPT DESIGN CHOICE | Propulsion- & Collection system



CONCEPT DESIGN CHOICE | Propulsion- & Collection system



CONCEPT DESIGN CHOICE | Propulsion- & Collection system



- **Objective Nodule Collection System:** develop a collector head with an appropriate PRODUCTION CAPACITY with MINIMAL ENVIRONMENTAL IMPACT, OPTIMAL PICK-UP EFFICIENCY and MINIMAL DOWNTIME.

- **Step 1: Define Design Drivers:**

- Production (X ton / year)
- $\eta_{pick-up} = M_{pick-up} / M_{Total}$ (Maximal)
- $Q_{water} \quad (= Q_{pick-up} + Q_{separation}) \sim E_{total}$
- Environmental impact:
 - $\downarrow \sim$
 - $\downarrow \sim$
 - $\sum T_{pick-up} + T_{separation} + T_{driving}$
 - Turbidity:*
 - Seabed disturbance*
 - Noise*
- Seabed interaction
- Reliability
- Lifetime



CONCEPT DESIGN CHOICE | Propulsion- & Collection system



► Step 2: Concept trade-off

Design drivers		Hydraulic collectors >	> Mechanical collectors ("Scraper" systems)
Pick-up efficiency	$\eta_{pick-up}$? 100%	? (~100%)
Water flow	$Q_{pick-up}$	↑	≈ 0
	$Q_{separation}$	≈ 0	↑
Environmental impact	$T_{pick-up}$	↑	↓
	$T_{separation}$	↓	↑
	$T_{driving}$	=	=
	Seabed disturbance	Top layer fluidized	Top layer sliced off
	Noise	Water pumps	Water pumps + drive
Seafloor interaction	-	↓ (No direct interaction)	↑ (Direct interaction)
Reliability	-	↑	↓ (More moving parts)
Lifetime		?	


End product =
Fluidized mixture



CONCEPT DESIGN CHOICE | Strategy


Step 1: Parallel collection-
and trafficability study

TSTD PATANIA I



TRL 4


LAB TESTS



TRL 4


Step 2: In-situ integrated test of
Pre-Prototype mining vehicle

PPV PATANIA II





TRL 5 – In situ

Step 3: In-situ System
Integration Test



Vessel: Orion (DEME)
Start construction: 2016



CONCEPT DESIGN CHOICE | Strategy




**Pre-Prototype
[2018 – 2019]**



**Tracked Soil Testing Device
[2016 – 2017]**

**Prototype
[2020 – 2023]**



PROCAT#1 | TSTD PATANIA I & COLLECTOR LAB TESTS

QUO
NON
DESCENDET?

“Until what depth will he not go?”

After the motto of Nicolas Fouquet (Superintendent of Finance of King Louis XIV) “Quo Non Ascendet”



PROCAT#1 | Tracked Soil Testing Device PATANIA I


- **Objective:** Design and build a TRACKED UNDERCARRIAGE suitable to do RESEARCH ON TRACK PERFORMANCE on the sea bed at 4,700 m below sea level.



- General trafficability objectives:
 - › Visual observation TSTD performance
 - › Speed , acceleration & slope
- Terramechanical objectives:
 - › Pressure – Sinkage relationship
 - › Shear stress – shear strain relationship (ex-situ)
 - › Thrust – slip relationship
- Environmental objectives:
 - › Turbidity by tracks
 - › Turbidity by horizontal water flow



PROCAT#1 | Tracked Soil Testing Device PATANIA I




- ▶ 9 dives and 25 days before 1st success
- ▶ Maximum Depth: 4.571m
- ▶ Total distance: 14,5km
- ▶ 24 sets of Pressure – Sinkage tests
- ▶ 42 Shear Stress – Shear Displacement tests (ex-situ)
- ▶ 0 Thrust – slip measurements (failure on connectors anchor load cells)



CONCEPT DESIGN CHOICE | Strategy


Step 1: Parallel collection-
and trafficability study

TSTD PATANIA I



TRL 4


LAB TESTS



TRL 4


Step 2: In-situ integrated test of
Pre-Prototype mining vehicle

PPV PATANIA II




TRL 5 – In situ

Step 3: In-situ System
Integration Test




Vessel: Orion (DEME)
Start construction: 2016





PROCAT#1 | Nodule Collection Laboratory Tests

- ▶ **Objective:** develop a collector head with an appropriate PRODUCTION CAPACITY with MINIMAL ENVIRONMENTAL IMPACT, OPTIMAL PICK-UP EFFICIENCY and MINIMAL DOWNTIME.

- ▶ Definition:



- ▶ 2 parallel CFD programs:
 - › Primary jet optimization
(no nodules / sediment)
 - › Pick-up process optimization
(with nodules / sediment)



PROCAT#1 | Nodule Collection Laboratory Tests

- **Laboratory Tests:** trade off between REPRESENTATIVENESS and “TEST SETUP”-REALITY



- 70m test flume (33m effective test length)
- Artificial nodules (tumbled lava stones)
 - › Nodule abundance 15 – 35 kg/m²
 - › 3 different sizes
- Artificial sediment (diluted loam)
 - › Loam vs. Clay vs. Bentonite
 - › Disregarded top “fluffy” layer (↓ T_{settling})
 - › No “added” nodule penetration



PROCAT#1 | Nodule Collection Laboratory Tests

- ▶ **Test procedure:** “Per geometrical configuration, changing one control parameter at a time”
 - › 9 Geometrical configurations
 - › 4 Control parameters
 - Speed of the carriage - v_{carriage}
 - 2 x Jet velocity (v_{PU} and v_{TR})
 - Height above the testbed
- ▶ In total 85 test runs (3 months)
- ▶ Maximum pick-up efficiency: 99%




PROCAT#1 | Movie



CONCEPT DESIGN CHOICE | Strategy


Step 1: Parallel collection-
and trafficability study

TSTD PATANIA I



TRL 4


LAB TESTS



TRL 4


Step 2: In-situ integrated test of
Pre-Prototype mining vehicle

PPV PATANIA II





TRL 5 – In situ


Step 3: In-situ System
Integration Test



Vessel: Orion (DEME)
Start construction: 2016



PROCAT#2 | PRE-PROTOTYPE VEHICLE PATANIA II



PROCAT#2 | INTEGRATED PRE-PROTOTYPE VEHICLE

► **Objective 1:** IN-SITU validation and optimization of the technology:

- › Nodule collection system ($\eta\% = f(v, H_{col}, Q_{jet}, \rho_{nod})$)
- › Trafficability (track performance, sinkage etc.)
- › Sensor suite (Multibeam, density meter etc.)

► **Objective 2:** ENVIRONMENTAL IMPACT EXPERIMENTS


- › Strip mining (mining impact experiment)
- › H_{col} vs. sediment pick-up
- › Mitigation systems (mudguards, diffuser etc.)
- › Input for hydrodynamic model (turbidity sensors)

► **Key Figures:**


- › Main Dimensions: L10m (+1m + 1m) x W4.7m x H4m
- › Mass: 35T.i.a. (incl. 3T payload nodules) ; 15T.s.
- › Total installed power: 400kW (4.2kV)



PROCAT#2 | INTEGRATED PRE-PROTOTYPE VEHICLE



PROCAT#2 | INTEGRATED PRE-PROTOTYPE VEHICLE



PROCAT#2 | INTEGRATED PRE-PROTOTYPE VEHICLE



- ▶ **Short term planning:**
 - › Mob. (EU): December 2018
 - › Tests (CCFZ): March - April 2019
- ▶ **Long Term Planning**
 - › Legislation: 2020
 - › System Integration test: 2022/23




COMPASS | ALGORITHM FOR AN OPTIMAL MINING PATH



COMPASS | ALGORITHM FOR AN OPTIMAL MINING PATH

► COMPASS : Control of an Operational Mining Path through an Auto-adaptive Steering System

- › Algorithm defining most optimal mining path
- › Technological challenges (System dynamics, technical limitations)
- › Environmental challenges (defining CEMS, Scale & Time)



Thank you for your attention



Questions?

